

PFT1300

PoE Extender



Features

- > Support passive PoE cascade power supply and Ethernet data exchange
- > Support IEEE 802.3af/at standard power supply IP Camera
- > Cooperate with PoE Extender (PFT1300), able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption $\leq 8W$), max transmission distance 300m
- > 1*RJ45 10/100M PoE power supply input; 1*RJ45 10/100M supply power for IP Cam; 1*RJ45 10/100M supply power for the next extender
- > Installation mode: junction box internal mounting, DIN rail mounting

Technical Specifications

| Model | PFT1300 |
|---------------|--|
| Ethernet port | 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC |

PFT1300

| | |
|-----------------------|---|
| Transmission Distance | Cooperate with DH-PFT1200, able to cascade level two extender, connect to 3 IPC (level one extender connects to 1 IPC, the OUT port of level two extender and CAMERA port connect to 1 IPC respectively, IPC power consumption $\leq 8W$), transmission distance is 300m |
| Power Consumption | $\leq 3W$ |
| Application Humidity | 10%—90% |
| High&Low temperature | - 30°C ~ 65°C |
| Weight | 57g |
| Dimension(W × D × H) | 79mm × 52mm × 23mm |

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.