

XIS-6545

High Performance System

Checkpoint Security: Baggage and Parcel Inspection





TRANSPORTATION

Airport entrances and perimeters, air cargo, and checkpoint technology.



PORTS & BORDERS

Border control, sea ports, and other large cargo sectors.



CRITICAL INFRASTRUCTURE

Access control for prisons, courthouses, mailrooms, hotel entrances and military bases.

The XIS-6545 is the ultimate X-Ray Inspection System with a tunnel opening of 65.1 cm x 45.4 cm (25.6" x 18"). Designed for small to medium sized objects, the XIS-6545 is the first product ever manufactured by Astrophysics and is characterized by its reliability, optimal dimensions and effective threat detection.

Ultimately, the XIS-6545 is a cost effective scanning solution for courthouses, prisons, hospitals and airport checkpoints with a standard 160kV generator.

Among the most commonly sold XIS units, the XIS-6545 is a quality checkpoint system featuring Astrophysics superior XIS software and maximized throughput.

All Astrophysics X-ray Inspection Systems are equipped with Real-Time Diagnostics, a unique Astrophysics feature which allows users to monitor system health. This software was specifically engineered to save you valuable time and money. If requested, Astrophysics would also be able to connect to your system and troubleshoot any issues remotely.

An exclusive Astrophysics option is our 6 Color Imaging, which enables operators to view screened objects in 6 colors, each color correlating to a specific range of Atomic Z-Numbers. 6 Color Imaging enables operators to achieve optimal material identification which improves throughputs.

Astrophysics is committed to providing quality products and services nationwide. We listen to our customers and offer customizations and order flexibility based on their needs.

Backed by a team of engineers from our City of Industry, California center of excellence headquarters, Astrophysics designs cutting-edge X-ray screening technology for detecting weapons and contraband for transportation, ports, borders, critical infrastructure and other industries that present security risks.

Astrophysics is headquartered in the United States and maintains a global presence with service delivery worldwide. Astrophysics is committed to global safety and is proud to present this new age of screening security—driving the industry into the technology of tomorrow.





GENERAL SPECIFICATIONS

• Tunnel Opening: 65.1 cm x 45.4 cm (W x H) 25.6" x 18"

• Dimensions: 216.4 cm x 87.3 cm x 131.6 cm (L x W x H) 85.1" x 34.3" x 52"

Shipping Dimensions: 231.1 cm x 102 cm x 159 cm (L x W x H) 91.3" x 40.1" x 63"
 Net Weight²: 515 kg (1135 lbs)
 Shipping Weight²: 710 kg (1565 lbs)

• Conveyor Speed: 23 cm/s (45 ft/min) Forward or Reverse

• Conveyor Height: 72.8 cm (28.7") from Floor

Conveyor Capacity: 165 kg (360 lbs) Evenly Distributed Load

TECHNICAL

Wire Resolution:
Spatial Resolution:
Steel Penetration:
Contrast Sensitivity:
Film Safety:
40 AWG Typical, 38 AWG Standard
1.0 mm Horizontal, 1.0 mm Vertical
39 mm Typical, 37 mm Standard
24 Visible Levels, 4096 Gray Level
Guaranteed up to ISO 1600 (33DIN)

X-RAY GENERATOR

Voltage: 160kV, Operating at 150kV
 Tube Current: 0.7 mA

Cooling: Sealed Di-Electric Oil Bath with Forced Air
 Duty Cycle: 100%, No Warm-Up Procedure Required
 Beam Direction: Diagonally Upward

• Detector: 1280 Channels in an L-Shaped Array

COMPUTER

Processor: Intel® Core i5, 3.1 GHz, 6MB cache
Memory: 4 GB RAM at 1333 MHz
Storage: 500 GB HDD
Video Card: 1 GB, Dual Digital Display
Platform: Windows® OS
Backup: Uninterruptible Power Supply

(Computer Operation - 20 Minute)

VIDEO

Display Type: Single 19" LCD Color Monitor
 Display Resolution: 1280 x 1024; 24 Bit/Pixel Color

ENVIRONMENTAL


 $\begin{array}{ll} \bullet \mbox{ Operating Temperature:} & 0^{\circ}\mbox{C} - 40^{\circ}\mbox{C} \setminus 32^{\circ}\mbox{F} - 104^{\circ}\mbox{F} \\ \bullet \mbox{ Storage Temperature:} & -20^{\circ}\mbox{C} - 60^{\circ}\mbox{C} \setminus -4^{\circ}\mbox{F} - 140^{\circ}\mbox{F} \\ \bullet \mbox{ Humidity:} & \mbox{ Up to 95\% Non-Condensing} \\ \end{array}$

ELECTRICAL

 Power Requirements: 110VAC±10%, 50/60Hz, 15 Amp Max 220VAC±10%, 50/60Hz, 10 Amp Max

HEALTH AND SAFETY

- Compliant with USFDA, Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)
- Typical radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by the Federal Standard)



STANDARD FEATURES

- 6 Color Imaging
- 9 Quadrant Zoom
- $\bullet \ \mathsf{Atomic} \ \mathsf{Z}\text{-}\mathsf{Number} \ \mathsf{Measurement}$
- Auto Image Archiving (150,000)
- Baggage Counter
- Color and Black/ White Imaging
- Continuous Scanning
- Continuous Zoom up to 64x
- Vertical Zoom Panning
- Geometric Image Distortion Correction
- · High Penetration Function
- · Heavy Duty Roller Casters
- · Image Annotation

- · Image Review
- Manual Bitmap Archive
- Material Discrimination
- Multi-Tier Accessibility
- Network Ready
- $\bullet \ \mathsf{Organic} / \ \mathsf{Inorganic} \ \mathsf{Imaging}$
- Operator Training
- Picture Perfect
- Print Image Capable
- Pseudo Color
- Real-Time Image Manipulation
- · Real-Time Self Diagnostics
- · Reverse Monochrome

OPTIONAL FEATURES³

- 24" LCD Monitor
- Computer Based Training (CBT)
- Custom Paint
- Density Alert
- Dual Monitors (19" LCD or 24" LCD)
- Entry/ Exit Roller Tables (50 cm Increments)
- Footmat Operator Interlock
- · Larger Heavy Duty Casters
- Local Language Support
- Polar Kit
- Radiation Meter
- Remote Workstation Configuration
- Screener Assist Software
- Test Case
- \bullet Threat Image Protection (TIP) Software
- Tropical Kit
- Wireless Barcode Scanning

GENERATOR UPGRADE

- · Upgrade to 180kV Generator
- Penetration: 41 mm Steel Typical, 39 mm Standard



¹ As tested on Astrophysics Inc. Test Piece.
² Weight of the system may vary depending on customization

weight of the system may vary depending on assonited to the system may stee that your Astrophysics Sales Representative for more information.

3 Optional features may affect lead time price, and weight of XIS-6545. Please contact your Astrophysics Sales Representative for more information.

⁴ Maximum Values on ASTM F792 Test Piece.

C E UKAS

Due to continued product research and development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice